

Bamboo Spa Enclosure Instruction Manual

Hardware Included:

9" Bolts – 8
 7 1/4" Bolts – 12
 6 1/2" Bolts – 16
 4 1/2" Bolts – 4
 3 1/3" Bolts – 12
 4" Bamboo slabs – 12
 T-Screws – 8

Roof Tiles – 8
 Bamboo Side Panels – 8
 Roof Support Beam (cover) – 8
 Roof Support Beam (bottom) – 8
 Pagoda top support Beam (cover) – 8
 Pagoda top support Beam (bottom) – 8
 Bamboo Peak Top – 1

1. Match panels with the letter-number codes on the inside of the panels.
2. Use 9" bolt to secure between the bottoms of conjoining panels. 4" Bamboo slabs are inserted into the opens slots below the bolts.



3. The T-screws will be screwed in between each panel at the top as pictured. Make sure the curve of the screws face inside of the enclosure. They will be used to secure the bamboo roof beams. Use 6 1/2" bolts to secure the top as well.



4. The gate is interlocked with a bolt and nut.



5. The beams will be attached at the 4 corners and 4 more in between the enclosure using the T-screws. Match the roof panels with the adjoining beams.



6. Use the 3 1/3" bolts to secure 4 of the bottom and cover pagoda top support beams with the smaller panels interlocked together.

